

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
A0		NEW		21.07.26

SPECIFICATIONS

Rated(额定参数): 300V,10A
Dielectric strength(抗电强度): AC2000V/1 Minute
Insulation Resistance(绝缘电阻):1000MΩ Min
Contact Resistance(接触电阻):20mΩ Max
Screw Torque(扭矩): 0.4Nm (3.5Lb.in)
Wire Range(线径):16~28AWG
Strip length(剥线长度):5~6mm
Temp. range(操作温度): -40℃~+105℃
MAX Soldering(瞬时温度):+250℃,5s

Housing Material(塑件): PA66 (UL94 V-0)
Contact(端子): Brass, Tin plating(黄铜镀锡)
Clamp(方块): Brass/Steel(铜/铁), Ni plating(镀镍)
Screw (螺丝): M2.5, Steel, Zinc plating(钢,镀锌)

PITCH RANGE IN MM			NOMINAL DIMENSION RANGE IN MM				
TO	OVER	OVER	TO	OVER	OVER	OVER	OVER
6	6	10	30	30	60	100	150
	TO	TO	TO	TO	TO	TO	TO
	10	24	30	60	100	150	150
±0.10	±0.15	±0.25	±0.30	±0.30	±0.50	±0.70	±1.00

Ordering Information




332K - 500 XX U 0 1

Pitch
500=5.0PH

No.of pins
2P,3P,4P~24P

Housing Color
B=Black
G=Green
U=Blue
R=Red
W=White
Y=Yellow
O=Orange
E=Grey

Packing
O=Pe bag
T=Tube
A=Tray



DRAW	SHUANGPING ZHENG	SCALE	FIT	 上海爱默电子科技有限公司 Tel: 86-21-37680290 Fax: 86-21-37680291	
		UNIT	mm		
CHECK	LICHAO LIU	SIZE	A4	PART NO.	332K-500XXU01
		SHEET	1/1	TITLE:	332K-5.0-XXP螺钉式端子台/PA66/蓝色
APPROVE	YONGLIANG GAO	PROJ.			